

## DECLARATION OF PERFORMANCE according to Regulation (EC) 305/2011 № 1-7-1-CPR-2013

1.Unique identification code of the product-type:

Roomheaters fired by solid fuel without hot water supply

EN 13240:2001/A2:2004/AC:2007

**FUOKO** 

2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):

Serial № (see rating label on the product).

3.Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Freestanding fireplace for intermittent burning without hot water supply, with firedoors closed.

4.Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):

SKLADOVA TEHNIKA

25 Sveti Knyaz Boris I Str., 5100 Gorna Oryahovitsa Republic of Bulgaria, E-mail: info@st-bg.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

6.System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7.In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Kontrol 94 Ltd.

61A Mladost Str., 5100 Gorna Oryahovitsa Republic of Bulgaria, Body: NB1879 Test report: K-10/12.06.2007

## 8. Declared performance:

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm sides=400 rear=400 front=800
Risk of burning fuel falling out	Pass
Emission of combustion products	CO [0.2650 %] wood; CO [0.1720 %] coal; dust [- mg/m³] NOx [- mg/m³] CxHy [- mg/m³]
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [318 C] wood; T [278 C] coal;
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output Room heating output	12 kW wood; 12 kW coal; 12 kW wood; 12 kW coal;
Water heating output	- kW
Energy efficiency	η [69.80%] wood; η [68.13%] coal;

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

01.07.2013 Gorna Oryahovitsa

Dimitar Nenov -CEO