

DECLARATION OF PERFORMANCE
according to Regulation (EC) 305/2011
No. 2014 - 002 – 0001

- | | |
|--|--|
| 1. Unique identification code of the product-type: | Room heaters fired by wood fuel without hot water supply
MAGIC ECO |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | Serial No (see rating label on the product): 00033 |
| 3. Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: | Appliance with intermittent and continues burning regime for operation with closed doors |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): | TIM SISTEM d.o.o.
Prva Berbernička str.No.9, Industrial area Nova Pazova
22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): | - |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: | KONTROL 94 Ltd
2 Mladost str. 5100 Gorna Oryahovitsa, Republic of Bulgaria,
Body ID : 1879 , Test report :NB 1879-K-11-2014 |

8. Declared performance:

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distance, in mm sides = 350, rear = 450, front = 1000
Risk of burning fuel falling out	Pass
Emission of combustion products	CO [0,0764%] Dust [35,8 mg/m ³] NOx [119,94mg/Nm ³] CxHy [76,49 mg/Nm ³]
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Clean ability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [270 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	6,90 kW
Room heating output	6,90 kW
Water heating output	- kW
Energy efficiency	η 78,79%

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

25.04..2014.


Ivan Stanković, CEO
