


**DECLARATION OF PERFORMANCE
according to Regulation (EC) 305/2011
No. 2015 - 24 – 0007**

- 1 Unique identification code of the product-type: Residential space heating appliance fired by wood pellets „RITTIUM 14 HYDRO“
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): Serial No (see rating label on the product): 03/2015 ser.00002
3. Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Appliance with intermittent and continues burning regime for operation with closed doors
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): **TIM SISTEM d.o.o.**
Prva Berbernička str.No.9, Industrial area Nova Pazova
22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): -
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **KONTROL 94 Ltd**
2 Mladost str. 5100 Gorna Oryahovitsa, Republic of Bulgaria,
Body ID : 1879 , Test report :NB 1879-K-05-2015-C
8. Declared performance:

| | |
|---|---|
| Harmonized technical specification | EN 14785:2006 |
| Essential characteristics | Performance |
| Fire safety | |
| Reaction to fire | A1 |
| Distance to combustible materials | Minimum distance, in mm sides = 200, rear = 300, front = 800 |
| Risk of burning fuel falling out | Pass |
| Emission of combustion products | CO max: 0,0053% |
| | Dust: 19,0 mg/m ³ |
| | NOx nom. :158,25mg/Nm ³ |
| | CxHy [- mg/m ³] |
| Surface temperature | Pass (operating tool) |
| Electrical safety | NPD |
| Clean ability | Pass |
| Maximum water operating pressure | - bar |
| Flue gas temperature at nominal heat output | T 124°C |
| Mechanical resistance (to carry a chimney/flue) | NPD |
| Thermal output | |
| Nominal heat output | 14,62 kW |
| Room heating output | |
| Water heating output | 10,32 kW |
| Energy efficiency | η 92,37 % |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

24.07.2015.


 Ivan Stanković, CEO

