



NB-No: 1837

ALFA PLAM

Radnička 1, 17501 Vranje, Serbia

BDS EN 16510-2-3:2023; DoP Alfa Term 35 02/26; Test Report: CPR 516/06.02.2026

ŠTEDNJAK ZA ETAŽNO GREJANJE

CENTRAL HEATING SOLID FUEL COOKER

Tip / Type	Alfa Term 35
Serijski broj / Serial number	26155150921006011
Datum proizvodnje / Mfg. date	apr 2026

Namena: Samostojeći štednjak za pečenje, pripremu hrane i grejanje prostora sa sistemom tople vode, sa zatvorenim vratima ložišta.
Intended use: Freestanding cooker for baking, food preparation, and space heating with hot water system, with a closed combustion chamber door.

Nosivost / Load bearing capacity 0 kg

Udaljenost u odnosu na zapaljive ugradne delove / Distance from the flammable installed components	$d_B = 0 \text{ mm}$
Udaljenost od dna / Distance to the bottom	$d_F = 0 \text{ mm}$
Udaljenost od poda ispred / Distance to the floor in front	$d_C > 750 \text{ mm}$
Udaljenost od plafona / Distance to the ceiling	$d_R = 300 \text{ mm}$
Udaljenost pozadi / Distance to the rear	$d_S = 400 \text{ mm}$
Udaljenost sa strane / Distance to the side	$d_L = 1500 \text{ mm}$
Udalj. od bočnog zračenja / Dist. to side radiation	$d_P = 1500 \text{ mm}$
Udaljenost spreda / Distance to the front	

Emisije pri / Emissions at	Minimal	Nominal
CO-Emisija / CO-Emission	NPD	1150 mg/m ³
NOx	NPD	88 mg/m ³
OGC (CxHy)	NPD	84 mg/m ³
Prašina / Dust	NPD	27 mg/m ³

Temp. dimnih gasova / Flue gas temp.	NPD	264 °C
Temp. izlaznih gasova / Flue gas outlet temp.	NPD	317 °C
Promaja dimnjaka / Chimney draught	NPD	20 Pa
Maseni protok dim. gas. / Flue gas mass flow	NPD	37,9 g/s

Toplota predata prostoru / Space heat output	NPD	10,3 kW
Toplota predata vodi / Water heath output	NPD	22,3 kW
Stepen iskorišćenja / Efficiency rate	NPD	76 %
Potrošnja el. energije / Electric power consumption	NPD	NPD

Potroš. energije u mirovanju / Power consumption in standby	NPD
Efikasnost grejanja prostora pri nominalnoj toplotnoj snazi / Space heating efficiency at nominal heat output	67 %
Indeks energetske efikasnosti / Energy-Efficiency index (EEI)	102
Klasa energetske efikasnosti / Energy-Efficiency class	A
Protivpožarna sigurnost instalacije do dimnjaka / Fire safety of installation to the chimney	T400 G

Koristiti samo preporučeno gorivo / Use only the recommended fuel

Dozvoljeno gorivo / Permitted fuel :	Cepano drvo / Fire Wood
Primenjeni standardi / Applied standards :	BDS EN 16510-1:2023
Nominalna toplotna snaga / Nominal heat output :	32,6 kW
Minimalna toplotna snaga / Part load heat output :	NPD
Tip uređaja / Type of the appliance	Type B
Maksimalni radni pritisak / Maximum operating pressure	1,9 bar
Informacije o radu / Operating information :	Povremeni rad / Intermittent operation
Prikladnost za zajednički dimnjak / Suitability for shared flue :	Ne / No

Obratiti pažnju i pročitati uputstvo za upotrebu
Pay attention and read the operations manual



NB-No: 1837

26



8 6 0 6 0 2 0 9 4 4 3 8 0

Boja
Colour
BELA
WHITE

Priključak
Connection
DESNO
RIGHT

MADE IN SRB

ŠTEDNJAK ZA ETAŽNO GREJANJE
CENTRAL HEATING SOLID FUEL COOKER

Alfa Term 35

Radnička 1, 17501 Vranje, Serbia



26155150921006011

Alfa Term 35



26155150921006011