

**DECLARATION OF PERFORMANCE  
according to Regulation (EU) 305/2011  
No. 1015-CPR-30-17512/TZ**

1. Unique identification code of the product-type: Room heaters fired by wood fuel without hot water supply  
**DIANA ECO**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): Serial No (see rating label on the product): 00032
3. Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Appliance with intermittent and continues burning regime for operation with closed doors
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): **TIM SISTEM d.o.o.**  
Prva Industrijska str.No.9, Industrial area Nova Pazova  
22 330 Nova Pazova, Serbia, **e-mail:** office@timsistem.rs
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): -
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **Strojirenský zkušební ústav, s.p**  
Hudcova 424/56b, Medlánky, 621 00 Brno, Česká republika  
Body ID : 1015 , Test report :30-17512/T

8. Declared performance:

Harmonized technical specification	EN 16510-2-1:2022
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distance, in mm sides = 800, rear = 500, front = 1500
Risk of burning fuel falling out	Pass
Emission of combustion products at nominal heat output in mg/m <sup>3</sup> at 13 % O <sub>2</sub>	CO 893 Dust 30 NO <sub>x</sub> 127 CxHy 61
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Clean ability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T 224 °C
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	5.1 kW
Room heating output	- kW
Water heating output	- kW
Energy efficiency	η 83,1%

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

07.02.2025.



Ivan Stanković, CEO  
NOVA PAZOVA