

Declaration of performance in accordance with Regulation (EU) No. 305/2011 of the European Parliament and of the Council

No.: TV-DoP-2025-07/EN

1. Unique product type identification code:

Wood fireplace stove **ANDORRA** and its design variants are appliances without a hot water supply, i.e. without an indirect heating function. Fireplace stoves meet the requirements of harmonized standards ČSN EN 16510-1 ed.2:2024, ČSN EN 16510-2-1:2025.

2. Type, series or serial number or any other element allowing identification of construction products:

ANDORRA wood fireplace stove and its design variants are designed for intermittent operation. The fireplace stoves have one heat output level, without room temperature control.

Basic technical data for wood fireplace stoves:

Type	Main dimensions (mm)			Nominal output (kW)	Fuel consumption (kg/h)	Diameter of flue gas (mm)	Operating pressure (Pa)
	Height	Width	Depth		Wood		
ANDORRA, type no. F 9489	1097	510	416	7.5	2.3	150	12
ANDORRA Exclusive, type no. F 9489 O*	1211	538	538				
ANDORRA Ceramic, type no. F 9489 6*	1256	538	460				
ANDORRA Serpentino, type no. F 9489 6*	1275	575	494				
SEVILLA, type no. F 9489 V*	1816	510	416				
DELIA, type no. F 9489 A*	1738	538	460				
CADIZ, type no. F 9489 C*	1468	538	460				
RODANO, type no. F 9489 P*	1250	510	416				
ATIKA, type no. F 9489 D*	1468	538	460				
ZION Ceramic, type no. F 9489 K*	1728	530	461				
ZION Serpentino, type no. F 9489 F*	1759	530	461				
ZION Steel (Stahl), type no. F 9489 L*	1728	530	461				
TOLEDO, type no. F 9489 J*	1256	535	454				
TOLEDO Exclusive, type no. F 9489 I*	1280	535	535				
ATIKA Steel, type no. F 9489 Q*	1468	530	456				

* Design variants differ only in their design.

Other data is provided in the catalogue of the manufacturer THORMA Výroba s.r.o., SK - Fil'akovo.

3. Intended use of the construction product in accordance with the relevant harmonized technical specification:

ANDORRA wood fireplace stove and its design variants are designed for supplementary reheating and heating of residential and communal rooms.

4. Name, company or registered trademark and contact address of the manufacturer:

Company name: **THORMA Výroba s.r.o.**
 Company registered office: **Šávoľ'ska cesta 1, 986 01 Fil'akovo, Slovak Republic**
 Company ID No.: **36030538**
 Telephone: **+421474511537**
 Fax: **+421474382289**
 E-mail: sales@thorma.sk

5. System for assessing and verifying the constancy of performance of construction products:

In accordance with harmonized standard EN 16510-2-1:2022, Annex ZA, Table ZA.2, System 3 applies to fireplace stoves.

6. The product is subject to the following harmonized standards:

ČSN EN 16510-1 ed.2:2024, ČSN EN 16510-2-1:2025 and assessment under System 3 was performed by Engineering Testing Institute, Public Enterprise, Hudcova 424/56b, CZ-621 00 Brno, notified body 1015 and issued:

- PROTOCOL on initial type examination of the product No. 30-17349/7/T, dated 2025-04-15

- PROTOCOL on assessment of properties, No. 1015-AoP-30-17349/7/TZ, dated 2025-04-25
- TEST CERTIFICATE, No. 0-B-00075-25, dated 2025-04-16

7. The declared properties stated in the declaration apply to all products listed in point 2:

Harmonized technical specification	ČSN EN 16510-1 ed.2:2024, ČSN EN 16510-2-1:2025	
Basic characteristics	Properties	
Fire safety - Reaction to fire	A 1	
Protection of flammable materials	Minimum distance from flammable materials [mm]	
	Front floor	1500
	Ceiling	>750
	Rear wall	ANDORRA, ANDORRA Exclusive, ANDORA Ceramic, ANDORRA Serpentino, SEVILLA, DELIA, CADIZ, RODANO, ATIKA, ZION Ceramic, ZION Serpentino, ZION Steel (Stahl), ATIKA Steel = 200, TOLEDO, TOLEDO Exclusive = 150
	Side	ANDORRA, ANDORRA Exclusive, ANDORA Keramik, ANDORRA Serpentino, SEVILLA, DELIA, CADIZ, RODANO, ATIKA, ZION Keramik, ZION Serpentino, ZION Steel (Stahl), ATIKA Steel = 450, TOLEDO, TOLEDO Exclusive = 250
	Side radiation area	1500
	Minimum distance from flammable materials	800
Risk of burning fuel falling out	Requirement met	
Combustion emissions	Parameter	Fuel: Wood
	CO (13% O ₂) [mg/Nm ³]	1000
	PM (13% O ₂) [mg/Nm ³]	23
	OGC (13% O ₂) [mg/Nm ³]	47
	NO _x (13% O ₂) [mg/Nm ³]	107
Surface temperature	Requirement met	
Electrical safety	NPD	
Cleanability	Requirement met	
Max. working pressure	NPD	
Mechanical resistance (load capacity of the exhaust pipe)	Requirement met	
Safety and accessibility during use		
Exhaust gas outlet temperature	298 °C	
Minimum chimney draft	12 Pa	
Exhaust gas mass flow	6.9 g/s	
Energy and heat savings		
Heat flow into the room	7.5 kW	
Heat flow into the water	NPD	
Heating efficiency	80 %	
Seasonal heating efficiency	70 %	
Energy efficiency index - EEI	107	
Energy efficiency classification - class	A	
Electricity consumption	NPD	
Energy consumption in standby mode	NPD	

8. The characteristics of the products listed in points 1 and 2 are in accordance with the characteristics listed in point 7, and their parameters comply with Commission Regulation (EU) 2015/1185 of 24 April 2015 (Ecodesign requirements for local solid fuels space heaters):

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Ing. Jaroslav Matúz, Director and Executive Officer
(name and position)


.....

Fil'akovo, 2025-09-30 (place and date of issue)

"NPD" (No Performance Determined) - the requirement does not apply to the product in question

