

DECLARATION OF PERFORMANCE according to Regulation (EU) 305/2011 No. 30-17815 / T

- | | |
|--|--|
| 1. Unique identification code of the product-type: | Room heaters fired by wood fuel without hot water supply
NORTH ECO |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | Serial No (see rating label on the product): 00014 |
| 3. Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: | Appliance with intermittent and continues burning regime for operation with closed doors |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): | TIM SISTEM d.o.o.
Prva Industrijska str.No.9, Industrial area Nova Pazova
22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): | - |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: | Strojirenský zkušební ústav,s.p
Hudcova 424/56b, Medlánky, 621 00 Brno, Česká republika
Body ID : 1015 , Test report : 30-18188/TZ |

8. Declared performance:

Harmonized technical specification	EN 16510-2-1:2022	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distance, in mm (NORTH) sides = 350; rear = 450 front = 1000	Minimum distance, in mm (NORTH WITH PANELS) sides = 0 rear = 300
Risk of burning fuel falling out	Pass	
Emission of combustion products at nominal heat output, in mg/m3 at 13% O2	CO 865	
	Dust 30	
	NOx 87	
	OGC 85	
Surface temperature	Pass (operating tool)	
Electrical safety	NPD	
Clean ability	Pass	
Maximum water operating pressure	- bar	
Flue gas temperature at nominal heat output	T [158 °C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	8,30 kW	
Room heating output	- kW	
Water heating output	- kW	
Energy efficiency	η 89,7 %	

28.10.2025.



Ivan Stanković, CEO